

CALIPER SPECIFICATION

BORE SIZE	38.10 x 41.30 (1.50"x1.625")
PISTON AREA / PAD	24.68 cm²
DISC DIA. MAX.	330.00
DISC THICKNESS MAX.	28.00
DISC THICKNESS MIN. (WORN CONDITION)	26.00 (DIFFERENTIAL WEAR NOT TO EXCEED 0.5mm SIDE TO SIDE)
WORKING PRESSURE	
HYDRAULIC FEED	M10 x 1.0
DRY WEIGHT (LESS PADS)	2.47 kg (ESTIMATED)
PAD FAMILY	
EFFECTIVE RADIUS (ON DIA. 330.00 DISC)	139.00
PL' DIMN.	60.36
OFFSET 'C' DIMN.	46.86
MTG. HOLE CENTRES 'D' DIMN.	152.00
PAD FRICTION MATERIAL MIN. THICKNESS	2.50
PAD RETENTION	LEDGES
TIGHTENING TORQUES	BLEED SCREW : 17Nm HYDRAULIC FEED : 25Nm RETAINER BOLT : 19Nm
CORROSION PROTECTION	FLUID RESISTANT PAINT FINISH – ALUMINIUM BODY. BOOT TYPE DIRT SEALS.

